

D21/D31



2" / 3" Thermal Label Printer



-
- Fashionable design
 - Space-saving, 30% smaller than traditional label printer
 - With optional Bluetooth 4.0 module
 - 448/640 dots support, 80mm maximum effective printing width
 - Built-in power adapter, only need power cable
 - Support large diameter paper roll and external paper inlet



SPECIFICATIONS



Model		D21	D31
Printing	Method	Direct Thermal	
	Resolution	203 dpi (8 dots/mm)	
	Speed	2ips ~ 4ips	
	Width	Max. 56 mm	Max. 80 mm
	Length	15mm ~ 300mm	
Programming Language		TSPL	
Media	Type	Roll or Fanfold label, die cut or continuous direct thermal labels, Tag stock, Continuous Receipt Paper	
	Diameter(Media Roll)	90mm	
	Thickness	0.003"(60 μm) ~ 0.007"(180 μm)	
Barcode	Linear Barcodes	CODE39, CODE93, EAN-8, EAN-13, EAN-2, EAN-5, UPC-A, UPC-E	
	2D Barcodes	QR Code	
Sensors	Gap Sensor	Transmissive (Fixed)	
	Other	Paper Out Sensor, Head-Up Sensor, TPH temperature detection	
Interface	Standard	USB Type B	
	Option	Bluetooth 4.0 (Factory installed)	
Power Adapter	Input	AC 100 ~ 240V, 50/60Hz	
	Output	DC 12V, 2A	
Reliability	TPH	50km	
Memory	RAM	2MB	
	ROM	2MB	
Softwares	Driver	Windows Vista/7/8/10 Windows Server 2008/Server 2012/Server 2016	
Options and Accessories		Bluetooth 4.0, External Label Roll Holder	
Physical Characteristics		182.5×134×120.6mm	210×154×135mm
Empty Weight		0.805kg	0.88kg
Agency Approvals		CCC, FCC, CE	

Applications: Retail, Consumer Goods, Pharmacy, Medical Record Labeling



HPRT
Your Future, Printed

Xiamen Hanin Electronic Technology Co.,Ltd.

ADD: 5F, 8# Building, Gaoqi Nan Shi'er Road, Aide Industrial Park,
Huli District, Xiamen, P.R China
TEL: +86-(0)592-5885993
FAX: +86-(0)592-5885992
WEB: www.hpert.com
EMAIL: mk@hpert.com

