

# MPT-II 2" Mobile Receipt Printer


- Extreme light , compact and portable
- Easy loading mechanism, easy maintenance
- Equipped with rechargeable 7.4V, 1500mAh Li-ion battery
- USB, RS232, Bluetooth communication interface
- Support client-side firmware upgrade
- Provide Windows driver
- Provide Win Mobile, WinCE, Android & IOS demo and SDK



Direct USB Charging(Optional)



Bluetooth Connection



Low Power Consumption

## Specification

Item	Parameter	
Printing	Printing Method	Direct Thermal Line Printing
	Resolution	203dpi (8dots/mm)
	Printing Speed	Max. 50mm/s
	Printing Width	48mm
	Interface	USB, RS-232, Bluetooth
Power Saving	Sleep Mode	YES
Memory	Flash	2 MB
Resident Fonts	Chinese	GBK16x16, 24x24dots
	Alphanumeric	ASCII: 8x16, 9x24, 12x24dots
	User-defined	YES
	Codepage	42
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code
Graphics	Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max.120K for total)	
Detection	Sensors	Paper out detection
LED indicator	Power Indicator	Red
	Error Indicator	Blue

Power	Input	AC 100 -240V
	Output	DC 12V/0.5A
	Battery	1500mAh/7.4V rechargeable Li-ion battery
Paper	Paper Type	Receipt Paper
	Paper Width	58mm
	Paper Thickness	0.056~0.1mm
	Paper Roller Diameter	≤40mm
	Paper Loading	Easy loading mechanism
Enviromtent	Operation	-5°C~50°C , 25%~80%RH
	Storage	-40°C~60°C, 5%~95%RH
Physical Characteristics	Dimension	102.5(L)*75(W)*45(H)mm
	Weight	279G (Without paper roll)
Options & Accessories		USB Cable, Paper Roll, Power Adapter, Leather Case, Power Cord, Quick Start Guide, CD
Software	Emulation	ESC/POS
	Driver	Windows
	SDK	WinCE, Win Mobile, Android, iOS

